Universal cleaning machine. LAAB.



Processing systems



Schmidt-Seeger TAS[™] 152A-2 / 154A-4 / 204A-4 / 206A-6. Schmidt-Seeger TAS[™] 153A-1 / 206A-2 / 210A-1 / 200A-III. Cleaning, grading, aspirating.

Conditioning and/or cleaning is an essential step at any grain or other bulk goods processing plant. The goal is to optimize the storage life of the grain and improve product quality. This step can prevent disease, improve the process flow and enhance production reliability.

Customer value

- High system availability
- Long service life
- High operational reliability
- Easy air volume regulation



LAAB - Cleaning, grading, aspirating.



High system availability Safety equipment such as the oscillation monitor on the screen box provide protection against system malfunctions.



High operational reliability Perforated screens with sturdy steel frames are kept clear by a service-proven rubber ball cleaning system.



Optional wear protection extends service life Rhino-Hyde lining on the cleaning machine provides optimum protection against wear and noise during operation.



Easy air volume regulation Air volume regulation on the machine and a vertical sifter with an adjustable cross-section and inspection windows ensure optimum cleaning quality for the products.

Flow rate	Up to 250 t/h (grain 0.75 t/m ³)	Energy consumption	Max. 3.75 kW
Screen area	Up to 48 m ²	Dimensions	Compact sizes
Screen changeover system	Available as an option	Dust removal	Aspiration at the inlet and outlet

Bühler GmbH Grain Logistics DE-92339 Beilngries, Germany T +49 8461 701 0 F +49 8461 701 133 grain-logistics@buhlergroup.com www.buhlergroup.com

Technical data

C BUHLER